

# PRODUCT DATASHEET



## 1. TECHNICAL DATA

<b>WEIGHT</b>	1100 gr.
<b>CAPACITY CUPS</b>	4 cups – 30cl
<b>MAXIMUN POWER ABSORPTION</b>	W 450
<b>VOLTAGE / FREQUENCY</b>	V ~ HZ 220 – 50/60
<b>COLOUR</b>	Green boiler, white uppe part, red lid/handle
	<p><u>Aluminum</u> suitable food contact</p> <p>The chemical composition of aluminum and aluminum alloys used are conform to the standards UNI EN 601/602 (Aluminum and aluminum alloys suitable food contact)</p>

Documento	Versione	Redatto	Data	
	01	Ufficio tecnico	20/03/2018	

	<b>PRODUCT DATASHEET</b>
--	--------------------------

<b>MATERIAL</b>	<u>Plastic</u> material (electric support base, handle, knob and lid)  The plastic materials used are conform to the standards DM 21-3-1973 (legislation concerning materials and articles in contact with foodstuffs)
	<u>Silicon</u> material (Gasket)  The silicon gasket used are conform to the standards DM 21-3-1973 (legislation concerning materials and articles in contact with foodstuffs)

Documento	Versione	Redatto	Data	
	01	Ufficio tecnico	20/03/2018	

# PRODUCT DATASHEET

## 2. DESCRIPTION OF THE APPLIANCE

The appliance is composed of the following components

<b>Pitcher lid</b>	Material: <u>Polycarbonate</u>
<b>Knob</b>	ABS
<b>Handle</b>	Nylon. Ergonomically handle designed for ensure the maximum safety when using the coffee-maker. This type of handle make it easy to carry and pour coffee.
<b>Boiler and upper part</b>	Material: <u>Aluminum</u> suitable foodstuffs contact (EN 601/602). The base of the boiler remains cold: you can place the coffee-maker everywhere
<b>Disk filter</b>	Material: <u>Aluminum</u> suitable foodstuffs contact (EN601/602)
<b>Gasket</b>	Silicon gasket
<b>Support base</b>	This component is fully compliant with the following standards:  <ul style="list-style-type: none"> <li>- CE 89/336 EEC (EMC)</li> <li>- CE 72/23 EEC (L.V.)</li> <li>- Directive 93/68 EEC</li> </ul> <p>The support base have a handle timer and electric connector. To avoid dangerous splashes of boiling water, never use the coffee maker unless the disk filter is correctly in position. Rest the coffee maker on the base. Closed the lid. In order to get the coffee, just turn right (clockwise).</p>
<b>Power cable</b>	Fully compliant to the Directive 93/68 EEC (V ~ HZ 220 – 50/60)  <ul style="list-style-type: none"> <li>- Place the appliance on a bench a bench away from water taps and sinks</li> <li>- Check that the voltage of the main power supply corresponds to the value indicated on the appliance rating plate. Only connect the appliance to a power outlet with a minimum rating of 6A that is properly earthed.</li> <li>- If the power outlet does not match the plug on the appliance, have the outlet replaced with a suitable type by qualified person.</li> </ul>
<b>Safety valve</b>	Opening pressure of safety valve: 2÷3,5 Bar (in according to UNI EN 13248:2004 - Cookware - Coffee makers for domestic use with an independent heat source -. Definitions, requirements and test methods)  Control parameter of safety valve (in according to UNI EN 2859/1): <ul style="list-style-type: none"> <li>- Type of sampling: attributes control</li> <li>- Sampling plan: Simple sampling</li> <li>- Sample units: safety valve</li> <li>- AQL Level: 0</li> </ul>

Documento	Versione	Redatto	Data
	01	Ufficio tecnico	20/03/2018

	<b>PRODUCT DATASHEET</b>
--	--------------------------

<b>Funnel filter</b>	<p>Material: <u>Aluminum</u> suitable foodstuffs contact (EN601/602).</p> <p>Dimensional control: conformity of the distance bottom/funnel in accordance with norm UNI EN 13248;2004 (§4.2.6) “Cookware. Coffee makers for domestic use with an independent heat source. Definitions, requirements and test methods”. Acceptance criterion: minimum distance allowed 2 mm</p>
<b>Coffee pod adapter</b>	<p>Material: <u>Aluminum</u> suitable foodstuffs contact (EN601/602).</p> <p>With silicon gasket</p>

Documento	Versione	Redatto	Data	
	01	Ufficio tecnico	20/03/2018	