

Description

It provides lubricants properties for metal/plastic, metal/rubber and plastic/plastic combinations, also suitable for metal/metal not subjected to high loads. It is not toxic, odorless and tasteless, and it is allowed for use with potable water.

Does not allow growth of fungus and moulds even in high humidity and temperature conditions.

It is not toxic, odourless and tasteless, it is allowed for use with potable water.

It is not flammable and has good electrical insulation properties.

It is strongly water-repellent and not easily removable from surfaces immersed in water. It does not allow growth of fungus and moulds even in high humidity and high temperature conditions.

Conforming to the military regulation MIL S8660B

Registered at NSF, cat. H1 for incidental contact with food, Reg. N. 141569.

Physical properties

Appearance :	translucent paste
Chemical composition :	dimethylpolysiloxane
Density @ +20°C :	ab. 1,00 g/ml
Penetration ASTM D217 :	200 - 260
Dielectric strength (CEI243) :	20 kV/mm
Dielectric constant at 1 KHz : (CEI 240)	2,80
Temperature range :	-40°C/+200°C
Drop point :	over +200°C
Flash point :	over +300°C
Volatility :	weght loss after 30 hours @ +200°C 2% max
Solubility :	not soluble in water, mineral and vegetal oils, acid and alkakine solutions, salts solutions. Easily removed by organic solvents.
Shelf life :	minimum 5 years in original unopened packaging

Storage

We recommend to store product in a cool and dry place at temperature non exceeding +25°C. After a long period of storage it is possible to find a light superficial sedimentation; it is enough to mix slightly before using.

To avoid contaminations do not refill containers with used product. For further information on applications, storage and handling contact Loxeal Technical Service

Safety and handling

Consult the Safety Data Sheet

Note

The data contained herein, obtained in Loxeal laboratories, are given for information only. Loxeal cannot assume responsibility for the results obtained by others which methods are not under Loxeal control. It is the user's responsibility to determine suitability for the user's purpose of any product mentioned herein. Loxeal disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Loxeal products. Loxeal specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.